



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, Ca 90638
 Phone: (562) 404-4474 * Fax: (562) 404-1773
 ssdi@ssdi-power.com * www.ssdi-power.com

SDAD102 UF Series

2,500 to 15,000 VOLTS ULTRA FAST RECOVERY STACKABLE HIGH VOLTAGE RECTIFIER

Designer's Data Sheet

Part Number/Ordering Information ^{1/}
 SDAD10 2

Screening ^{2/}
 ___ = Not Screened
 TX = TX Level
 TXV = TXV Level
 S = S Level

Reverse Recovery Time
 UF = Ultra Fast Recovery Time

Voltage 2.5 = 2.5kV, 5 = 5kV,
 7.5 = 7.5kV, 10 = 10kV, and 15 =
 15kV

Power Rating (See Below)

Package Size = 2 Inches Diameter

- FEATURES:**
- Stackable to 600 kV+
 - PIV 2.5kV to 15kV
 - High Current Ratings
 - Ultra Fast Reverse Recovery Time
 - Only Hermetically Sealed Rectifiers Used
 - Controlled Avalanche Rated
 - Modular Design for Easy Stacking
 - Storage and Operating Temps -65°C to +150°C
 - Available in Standard, Fast and Hyper Fast Versions
 - TX, TXV, and S-Level Screening Available ^{2/}

ELECTRICAL CHARACTERISTICS ^{3/}

Part Number	Peak Inverse Voltage	Reverse Recovery Time ^{5/}	Average DC Output Current ^{4/} Tc = Case Temperature			Surge Non-repetitive	Maximum Forward Voltage Drop		Maximum Leakage Current @ PIV
	PIV (KV)	Max (ns)	If(avg)			Ifsm	Vf (V)	If (A)	Ir (uA)
	25 °C	25 °C	75 °C	50 °C	60 °C	100 °C	25 °C		25 °C
SDAD102 H 2.5 UF	2.5	70	9.00	10.6	10.0	200	4.35	6.3	30
SDAD102 H 5.0 UF	5.0	70	6.60	8.80	8.00	200	7.92	4.5	30
SDAD102 H 7.5 UF	7.5	70	2.00	3.00	2.50	125	10.9	1.5	15
SDAD102 H 10 UF	10	70	1.50	2.00	1.80	100	13.6	1.2	15
SDAD102 H 15 UF	15	70	1.00	1.40	1.20	100	18.9	0.7	15

SDAD102 Package:

NOTES:

- 1/ For Ordering Information, Price, Curves, and Availability- Contact Factory.
- 2/ Screening based on MIL-PRF-19500. Screening flows available on request.
- 3/ Unless Otherwise Specified, All Electrical Characteristics @25°C.
- 4/ Tc = 50 °C typical operation in oil.
Tc = 75 °C is typical ambient Ta = 25 °C unheatsunk.
Tc = 60 °C typical operation with extender plates in air.
- 5/ Recovery Conditions: If = 0.5 Amp, Ir = 1.0 Amp rec. to .25 Amp.

