



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, Ca 90638
 Phone: (562) 404-4474 * Fax: (562) 404-1773
 ssdi@ssdi-power.com * www.ssdi-power.com

Designer's Data Sheet

Part Number / Ordering Information ^{1/}

SRH **F** **Screening**^{2/} **Package** **Recovery Time** **Voltage**

_____ = None
 TX = TX Level
 TXV = TXV Level
 S = S Level

_____ = Axial
 SMS = Surface Mount Square Tab

F = Fast

20 = 2,000 V
 25 = 2,500 V
 30 = 3,000 V

SRH20F thru SRH30F Series

1.5 AMP
2,000 - 3,000 VOLTS
FAST RECOVERY
HIGH VOLTAGE RECTIFIER

FEATURES:

- Fast Recovery: 180 nsec Maximum
- PIV to 3 KV
- Hermetically Sealed Axial and Surface Mount Package
- Void-Free Ceramic Frit Glass Construction
- High Temperature Category I Eutectic Metallurgical Bond
- Excellent Thermal Shock Performance
- For use in high voltage systems
- 175°C Maximum Operating Temperature
- Smaller-sized Replacement for 1N6512 thru 1N6515 and 1N6520 thru 1N6523 in Many Applications
- TX, TXV, and Space Level Screening Available^{2/}
- Available in Ultra Fast and Hyper Fast Versions. Contact Factory.

ELECTRICAL CHARACTERISTICS

Part Number	Peak Inverse Voltage	Average Rectifier Current		Maximum Reverse Current		Maximum Forward Voltage	Maximum Surge Current (see note 8)	Maximum Reverse Recovery Time	Maximum Junction Capacitance	Typical Thermal Resistance	
Symbol	PIV	I _O		I _R		V _F	I _{FSM}	t _{RR}	C _J	R _{θJE}	R _{θJL}
Units	Volts	A		μA		Volts	Amps	nsec	pF	°C/W	
Conditions		25°C	100°C	25°C	100°C	25°C	25°C	25°C	V _R = 100V f _T = 1MHZ		L = 1/8"
SRH20F	2000	1.5	1.0	0.5	10	6.0	60	180	10	4	8
SRH25F	2500	1.5	1.0	0.5	10	6.0	60	180	10	4	8
SRH30F	3000	1.5	1.0	0.5	10	6.0	60	180	10	4	8

1/ For ordering information, price, and availability – Contact factory.

2/ Screening based on MIL-PRF-19500. Screening flows available on request.

3/ Operating and testing over 10,000 V/inch may require encapsulation or immersion in a suitable dielectric material.

4/ I_F = I_O; Max. forward voltage measured with instantaneous forward pulse of 300μsec minimum.


5/ Max. Lead/End Tab temp. for soldering is 250°C, 3/8" from case for 5 sec maximum.

6/ Operating and storage temperature: -65°C to +175°C.


7/ Reverse recovery test conditions: I_F=0.5A, I_R=1.0A, I_{RR}=0.25A, T_A=25°C.

8/ Surge at 1 ms square pulse. 1 cycle.

Axial



Surface Mount Square Tab



This device is a replacement for SSDI's SDH20F through SDH30F family of devices.
This device offers superior performance in V_F & I_R.

NOTE: All specifications are subject to change without notification.
 SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RC0167A

DOC




Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, Ca 90638
Phone: (562) 404-4474 * Fax: (562) 404-1773
ssdi@ssdi-power.com * www.ssdi-power.com


SRH20F thru SRH30F Series

PACKAGE OUTLINE: Axial



DIMENSIONS		
DIM	MIN	MAX
A	—	0.150"
B	0.200"	0.240"
C	0.048"	0.052"
D	1.00"	—

PACKAGE OUTLINE: Surface Mount Square Tab



DIMENSIONS		
DIM	MIN	MAX
A	0.170"	0.180"
B	0.250"	0.295"
C	0.020"	0.030"
D	0.002"	—

Notes:

Consult manufacturing for operating curves.